

### mineral tile

For use with - Ceramic Tiles, Terrazzo, Quarry Tile, Slate, Granite, Polished Stone, Travatine and most Marbles

## Introduction

4Earth Anti Slip Mineral Tile is completely eco friendly containing less Glycolic acid than that of ladies make up !

Because in most cases it will not change or damage the aesthetics of a floor you can now win the orders you previously may have had to walk away from.

Safer floors mean less risk of slips, trips or falls and avoidance of costly compensation claims.

Following 4Earth Solutions application formula the highest slip resistance values can be achieved.

Proven Durability - **GUARANTEED** you are safe in the knowledge that our anti-slip treatment will last for many years subject to a suitable cleaning regime, **4Earth Anti Slip Mineral Tile is guaranteed for 5 years.**

Due to the fact that the surface roughness does not change the application of 4Earth Anti Slip means no extra work and therefore expense to add to the cleaning regime

- Unsurpassed Slip resistance has achieved up to 70 Wet PTV (Pendulum Test Value)
- Eco friendly
- NO Acid etching (will not damage a floor)
- Easy Maintenance and Cleaning
- Proven Durability (up to 64,000 footfall per hour)

## Application

### Easy, Fast and Profitable to apply

It is possible for an experienced 2-3 man team to cover up to 1,000 square metres in an 8 hour shift\*

Your existing anti slip applicators will love how easy it is to get great results and you will have a very loyal customer.

**4Earth Anti Slip IS NOT A COATING** it is a treatment that is simply washed onto the surface and washed back off again. The treatment achieves a Co efficiency of friction that will delight your customer.

Pendulum Test Values (PTV) of up to 70 are not uncommon, subject to material (The Health and Safety Executive ,UK recommends 36 PTV)

It is possible to achieve a 36 PTV within 30 minutes of commencing treatment As soon as the floor is dry it is able to be walked on!

For further details see our "**Application Method guide**"

1 Litre can cover between 4 and 8 square metres depending on the tile. (For further details please ask 4Earth Solutions for guidance)

4Earth Solutions now consult with World renowned Architects and institutions

\*subject to suitable training, experience and equipment used.



# “4Earth Anti Slip An Anti Slip but not anti slip as you know it!”

## Superb Technical back up and support from a world wide brand

4Earth Solutions are on hand to provide all the technical support and back up you require.

We can advise on the correct dilution ratios for different materials.

Just send us a sample of the floor surface you wish to be treated and we will send and if necessary even create the correct solution for the specific job.

## Typical Results

	Health and Safety Executive Recommended	Before Treatment	After 4Earth Anti Slip
COF - When Dry	36PTV	55 PTV	60 PTV
COF - When Wet	36PTV	12 PTV	45-70 PTV*

(PTV - Pendulum Test Value)  
(COF - Coefficient of Friction)

\*Depending on material

## Packaging

4Earth Anti Slip is available in the following sizes :

1 Litre, 5 Litre, 25 Litre



+44 (0) 191 567 0300

info@4earthsolutions.com

www.4earthsolutions.com

**4** Earth Solutions  
A Safer Cleaner World

4Earth Solutions Ltd, The Mowbray Centre,  
2 Tavistock Place, Sunderland, SR1 1PB  
United Kingdom