

### Awesome Anti Slip, Superb Sealer!

At last an anti slip for decking that works.

4Earth Anti Slip for Decking is a clear coating that provides excellent slip resistance and maintains a great looking deck.

Independently tested and verified to UKAS BS 7976 a wet PTV (Pendulum Test Value) of 39 (UK Health and Safety Executive requires 36)

Ensure maximum floor safety on wet timber decking with 4Earth Anti Slip for Decking

4Earth Anti Slip provides the same quality performance used by organisations such as London Underground, Bombardier Transportation and contractors throughout the world.

It protects and waterproofs decking from the harmful effects of rain, frost and UV rays whilst resisting cracking, peeling and flaking.

- Excellent durability, 3 - 10 years
- Helps protect and prolong the life of the decking
- Textured to create an anti slip finish
- Will resist UV fading and discolouration
- Excellent resistance to chemical spillage
- Easy to apply with a soft bristle brush
- Flexible to resist cracking
- Excellent abrasion resistance
- In dry conditions can be applied in temperatures ranging from 5°C



Before                      After  
4Earth Anti Slip for Decking example



In addition to the clear finish the following colours are also available\*:

### Specifications

**Areas of use:**

Hardwood and soft wood decking

**Coverage:**

4-8 square meters per litre

**Number of coats:**

1 or 2 depending on desired finish and surface

**Application:**

Brush

**Protection level:**

High

**Drying time:**

3 hours




Clear




Walnut



Terracotta



Olive Green



Charcoal Grey



Mahogany

\*Colours may vary to what is shown



4Earth Anti Slip

An Anti Slip but not anti slip as you know it!



## Application

Mechanical equipment must be checked for defects prior to commencement. Any defects, which cannot be repaired on site, must be reported immediately to the Team Leader. Faulty or defective equipment or machinery should not be used.

PPE should be worn at all times.

Cordon off work areas by means of cones and barriers to create a safety zone. Use "No Entry" or "Caution Works In Progress" warning signs at entry and exit points.

If goggles or dust masks, or respirator masks become contaminated wash thoroughly before putting on and replace filters if applicable.

Clean the area to be treated with a floor scrubbing machine or manually with a mop and bucket using 4Earth Safe Clean Plus (refer to dilution chart) for application requirements or if required 4Earth Mop and Strip. Make sure that all dirt, surface grease and contaminants such as moss and algae are removed from the surface. For excellent moss and algae removal please consult 4Earth Solutions.

If deep cleaning is required, repeat process and increase dilution mix as required. Spot clean stubborn stains with concentrate on a micro sponge until the surface is as required.

Residue and excess liquid is to be removed from the surface. Disposal of waste should comply with local authority environmental controls and comply with COSHH Assessments.

4Earth Anti slip for Decking, is supplied in either 5 litre or 20 litre metal containers with the poly bead supplied separately. First ensuring that you are wearing a mask, thoroughly mix the poly beads together with the anti slip in a tub by mechanical means.

### Coverage:

5 litres will cover between 20 and 40 square meters depending on the desired finish (1 Coat).

### Application:

Pour mix into a paint scuttle and apply evenly apply using a wood decking paint brush. Take care not to pool and so avoid solution settling into grooves.

Apply a second (and subsequent coats) if required. Please note it is possible that a third and subsequent coats will enhance the gloss finish but may reduce slip resistance.

If additional coats are required wait until touch dry or the 3 hour cure period.

### Drying time:

Foot traffic 3 hours, vehicular 24 hours

Ensure site is clean and floor treatment is fully dry before removal of safety barriers and all equipment removed and safely stored.

### Co-ordination with others

Other contractors using the common access and egress points should be advised of the work in progress. The detailed programme will be discussed with these contractors to ensure safe working procedures are in place and safety is not compromised.



+44 (0) 191 567 0300



info@4earthsolutions.com



www.4earthsolutions.com

**4Earth Solutions**  
A Safer Cleaner World

4Earth Solutions Ltd, The Mowbray Centre,  
2 Tavistock Place, Sunderland, SR1 1PB  
United Kingdom