

٦

Safety Data Sheet ULTRATOP BIANCO

Γ

ECTION 1: Ide	
	ntification of the substance/mixture and of the company/undertaking
1.1. Product	
	ication of the substance:
	name: ULTRATOP BIANCO
	t identified uses of the substance or mixture and uses advised against nmended use:
	nt based levelling mortar.
	nt based levelling mortar.
	advised against:
==	-
	of the supplier of the safety data sheet
Suppl	
	I U.K. Ltd - Mapei House Steel Park Road owen - West Midlands B62 8HD
	person responsible for the safety data sheet:
	zza@mapei.it
	ncy telephone number
	il Ú.K. Ltd - phone: +44(0)121 508 6970
	fax: +44(0)121 5086 960
	www.mapei.co.uk (office hours)
	Symbols: roduct is not a hazardous article and need not be labelled according to EC Directive 8, 99/45 as amended.
	sicochemical, human health and environmental effects: ner hazards
2.2. Label el	ements
Special Prov	
Sofot	v data sheet available for professional user on request.
Salety	
Special prov None	isions according to Annex XVII of REACH and subsequent amendments:
Special prov None 2.3. Other ha	azards
Special prov None 2.3. Other have vPvB	azards Substances: None - PBT Substances: None
Special prov None 2.3. Other ha vPvB Other Hazar	azards Substances: None - PBT Substances: None ds:
Special prov None 2.3. Other ha vPvB Other Hazar No otl	azards Substances: None - PBT Substances: None ds: her hazards
Special prov None 2.3. Other ha vPvB Other Hazar No oth See a This p	azards Substances: None - PBT Substances: None ds:
Special prov None 2.3. Other ha vPvB Other Hazar No oth See a This p fluids)	azards Substances: None - PBT Substances: None ds: her hazards t paragraph 11 the additional information concerning crystalline silica reparation contains cement. Contact between cement and body fluids (e.g. sweat and ey may cause irritation or burns.
Special prov None 2.3. Other ha vPvB Other Hazar No oth See a This p fluids)	azards Substances: None - PBT Substances: None ds: ner hazards t paragraph 11 the additional information concerning crystalline silica reparation contains cement. Contact between cement and body fluids (e.g. sweat and ey may cause irritation or burns.



3.2. Mixtures
 Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and corresponding classification: 50% - 75% free crystalline silica (Ø > 10 μ) CAS: 14808-60-7, EC: 238-878-4
2.5% - 5% Portland cement, Cr(VI) < 2 ppm CAS: 65997-15-1, EC: 266-043-4 Xi; R36/37/38
SECTION 4: First aid measures 4.1. Description of first aid measures In case of skin contact: Wash with plenty of water and soap. In case of eyes contact:
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:
Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet. In case of Inhalation:
Remove casualty to fresh air and keep warm and at rest.
4.2. Most important symptoms and effects, both acute and delayed
No specific hazards are encountered under normal product use.
This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye
fluids) may cause irritation or burns. 4.3. Indication of any immediate medical attention and special treatment needed
Treatment:
(see paragraph 4.1)
SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media:
Carbon dioxide (CO2).
Extinguishing media which must not be used for safety reasons:
None in particular.
5.2. Special hazards arising from the substance or mixture
The product does not present a fire hazard
5.3. Advice for firefighters Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into
drains.
Move undamaged containers from immediate hazard area if it can be done safely.
SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8. 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
905S400/1
Page n. 2 of 8



6.3. Methods and material for containment and cleaning up
Rapidly recover the product, wearing protective clothing.
Scoop into containers and seal for disposal.
After the product has been recovered, rinse the area and materials involved with water.
6.4. Reference to other sections
See also section 8 and 13
SECTION 7: Handling and storage
7.1. Precautions for safe handling
Avoid contact with skin and eyes and exposure to high dust concentration.
Avoid powder development and deposit
Do not eat or drink while working.
See also section 8 for recomened protective equipment.
7.2. Conditions for safe storage, including any incompatibilities
Always keep the containers tightly closed.
Incompatible materials:
Keep away from water or from damp surroundings.
Instructions as regards storage premises:
Adequately ventilated premises.
7.3. Specific end use(s)
None in particular
SECTION 8: Exposure controls/personal protection
8.1. Control parameters
free crystalline silica ($\emptyset > 10 \mu$) - CAS: 14808-60-7
TLV TWA: - 0,025 mg/m ³ (respirable fraction)
Portland cement, Cr(VI) < 2 ppm - CAS: 65997-15-1
TLV TWA: - (polvere)10 mg/m ³
DNEL Exposure Limit Values
N.A.
PNEC Exposure Limit Values
N.A.
8.2. Exposure controls
Eye protection:
Safety goggles.
Not needed for normal use. Anyway, operate according good working practices.
Protection for skin:
No special precaution must be adopted for normal use.
Protection for hands:
Not needed for normal use.
Respiratory protection:
Not needed for normal use.
Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves
and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the
suitability of equipment against specific chemicals and for user information.
Thermal Hazards:
None
Environmental exposure controls:
None



SECTION 9: Physical and chemical p	properties
9.1. Information on basic physical an	
Appearance:	powder
Colour:	various
Odour:	slight, typical of cement
Odour threshold:	N.A.
pH:	N.A.
pH(water dispersion,10%):	11
Melting point / freezing point:	N.A.
Initial boiling point and boiling	
Solid/gas flammability:	N.A.
Upper/lower flammability or ex	
Vapour density:	N.A.
Flash point:	n.⊲. == ℃
•	C N.A.
Evaporation rate:	N.A. N.A.
Vapour pressure:	
Relative density:	2 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	partly soluble
Solubility in oil:	insoluble
Viscosity:	N.A.
Auto-ignition temperature:	Ĵ° ==
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol,	,
Explosive properties:	
Oxidizing properties:	N.A.
9.2. Other information	
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant pr	operties N.A.
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Stable under normal condition	S
10.2. Chemical stability	
Stable under normal condition	S
10.3. Possibility of hazardous reaction	ins
10.4. Conditions to avoid	
Stable under normal condition	S.
10.5. Incompatible materials	
None in particular.	
10.6. Hazardous decomposition proc	lucts
None.	
SECTION 11: Toxicological informat	ion
11.1. Information on toxicological eff	
	5010
Route(s) of entry:	
Ingestion: Yes	
Inhalation: Yes	
Contact: No	
Toxicological information related to t	
Toxicological information of th	e mixture:
905S400/1	

905S400/1 Page n. 4 of 8



N.A. Toxicological information of the main substances found in the mixture:
N.A. Corrosive/Irritating Properties:
Skin:
The product can cause irritation by contact.
Eye: The product can cause irritation by contact
Sensitizing Properties:
No effects are known. Cancerogenic Effects:
The IARC (International Agency for Research on Cancer) believes that the crystalline silica
inhaled at the workplace can cause lung cancer in man. However, it also points out that the cancer effect depends on the silica characteristics and on the
biological-physical condition of the environment.
There is a large amount of information in support of the fact that increased risk of cancer is limited to persons suffering from silicosis.
In the current situation of studies, protection of workers from silicosis can be ensured by
respecting the exposure limit values.
Mutagenic Effects:
No effects are known. Teratogenic Effects:
No effects are known.
Additional Information:
Contains cement. Cement gives a strong alkaline reaction with water and body fluids (e.g. sweat and eye fluids), therefore the contact with skin and eyes should be carefully avoided.
If not differently specified, the information required in Regulation 453/2010/EC listed below must be
considered as N.A.: a) acute toxicity;
b) skin corrosion/irritation;
c) serious eye damage/irritation;
 d) respiratory or skin sensitisation; e) germ cell mutagenicity;
f) carcinogenicity;
g) reproductive toxicity; h) STOT-single exposure;
i) STOT-repeated exposure;
j) aspiration hazard.
SECTION 12: Ecological information
12.1. Toxicity
Not available data on the mixture Adopt good industrial practices, so that the product is not released into the environment.
N.A.
12.2. Persistence and degradability N.A.
12.3. Bioaccumulative potential
N.A. 12.4. Mobility in soil
N.A.
12.5. Results of PBT and vPvB assessment 905S400/1
Page n. 5 of 8



12.6.	vPvB Substances: None - PBT Other adverse effects			
	Not available data on the mixtu	re		
SECTION 13: Disposal considerations 13.1. Waste treatment methods Recover if possible. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.				
	14: Transport information			
14.1.	UN number UN Number:			
14.2	UN proper shipping name	==		
14.2.	N.A.			
14.3.	Transport hazard class(es)			
	Rail/Road(RID/ADR):	no dangerous good		
	ADR-Upper number:	NA		
	Air (ICAO/IATA):	no dangerous good		
	Sea (IMO/IMDG):	no dangerous good		
111	N.A. Packing group			
17.7.	N.A.			
14.5.	Environmental hazards ADR Enverinmental Pollutant:			
	Marine pollutant:	(powder)10		
14.6.	N.A. Special precautions for user			
	N.A.			
14.7.	Transport in bulk according to A No	nnex II of MARPOL73/78 and the IBC Code		
SECTION '	15: Regulatory information			
	Safety, health and environmenta Dir. 67/548/EEC (Classification	al regulations/legislation specific for the substance or mixture , packaging and labelling of dangerous substances) ackaging and labelling of dangerous preparations) chemical agents at work)		
	Regulation (EC) n. 1907/2006 (Regulation (EC) n. 1272/2008 (Regulation (EC) n. 790/2009 (A	CLP) ATP 1 CLP)		
	Regulation (EU) n. 453/2010 (A ictions related to the product or t 1907/2006 (REACH) and subset None	the substances contained according to Annex XVII Regulation		
REAC	CH Regulation (1907/2006)			
	CH Regulation (1907/2006) – Al product contains Cr (VI) under t	I. XVII he limitse established by annex. XVII pt.47. Respect the duration		
905S400/1				
Page n. 6 o	f 8			



according to the information described on the packaging REACH Regulatio n°1907/2006 (REACH) – Art. 59 (Substances in "Candidate List"): N.A. CLP Regulation n°1272/2008 (CLP) and s.m.i. Directive n°1999/45/CE (Dangerous Preparation) and s.m.i. Directive n°67/548/CEE (Substances) and s.m.i. Directive 2000/39/CE and s.m.i. (Professional threshold limit) Directive 105/2003/CE (Seveso III): N.A. ADR Agreement – IMDG Code – IATA Regulation Wassergefährdungsklasse: VOC (2004/42/EC) : N.A. g/l Social Dialogue on Respirable Crystalline Silica On April 26, 2006 was signed a multi-sector social dialogue, based on a "Guide to Good Practices", on workers health protection who are in contact with products containing crystalline silica. The text of the agreement published in G.U. European Union (2006 / C 279/02) and the "Guide to Good Practices", with attachments, are available on www.nepsi.eu website, they offer guidelines and useful information for handling products containing respirable crystalline silica. 15.2. Chemical safety assessment No **SECTION 16: Other information** Text of phrases referred to under heading 3: R36/37/38 Irritating to eyes, respiratory system and skin. This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU. This document was prepared by a competent person who has received appropriate training. Main bibliographic sources: NIOSH - Registry of toxic effects of chemical substances ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities SAX'S - Dangerous properties of industrial materials Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. This MSDS cancels and replaces any preceding release. 905S400/1 Page n. 7 of 8



ADR:	European Agreement concerning the International Carriage of
0.1.0	Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"
	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA	Threshold Limit Value for the Time Weighted Average 8 hour day.
	(ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	