

Indoor - Medium traffic

199 Logo Mat



Indoor - Medium traffic

199 Logo Mat

The Logo Mat high quality multi-functional dust control mat is densely tufted with an open Frieze tuft for true depth of colour and a trackless surface to ensure a high water absorption capacity and dirt removal for a highly effective solution. A durable vinyl backing with a smooth finish adapts to any surface.

This logo Mat can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Artwork is supplied within 24-hours. The mat is printed 24 hours after the artwork approval is given.

Recommended use:

- Medium traffic
- For loose lay placement

Specifications:

- 100% polyamide 6.6 yarns
- Backing: Black vinyl (DOP free)
- Vinyl borders: 2.5 cm on all sides
- Overall thickness: 8 mm
- Weight: 3 kg/m²
- Fire rating EU: Bfl-S1
- Special characteristics: Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals

Recommended accessories:

- 083 Bevelled Nosing 2 mm

Standard sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
- 120 cm x 240 cm

Custom lengths:

- 135 cm x linm
- 150 cm x linm
- 200 cm x linm

Colours:

- Unlimited colour possibilities

Cleaning instructions:

- Vacuum clean



PRODUCT TESTING

Water Retention

Crush

Resistance

Dust Control

199 Logo Mat

Art. nr.	Dimensions	Weight kg
199S0023WH	60 cm x 90 cm	1,5
199S0034WH	90 cm x 120 cm	2,9
199S0035WH	90 cm x 150 cm	3,4
199S0046WH	120 cm x 180 cm	5,5
199S0048WH	120 cm x 240 cm	10,1
199C0051WH	135 cm x linm	3,4
199C0060WH	150 cm x linm	4,5
199C0078WH	200 cm x linm	6



199 Logo Mat

GENERAL DESCRIPTION

Designation	Logo Matting
Type	Indoor Absorbant - Printed Logo Mats
Description	199 Logo Mat can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.
Surface	Smooth even surface
Category	Logo Matting
Recommended use	Indoor Medium traffic
Colours	Unlimited colour possibilities
Edges	Vinyl borders: 2.5 cm on all sides

TECHNICAL SPECIFICATIONS

Material	100% polyamide 6.6 yarns
Backing	Black vinyl (DOP free)
Primary backing	Nonwoven PET/PA
Process	Tufting
Yarn Construction	Cut loop pile - frieze
Pile weight	700 g/m ²
Total weight	3 kg/m ²
Pile height	0,66 mm
Overall thickness	8 mm

TESTS

Absorption capacity	TNO W6034	4 l/m ²
Fire rating EU	EN 13501	Bfl-S1
Static charge	ISO 6356	<0.1
Comfort class	EN 1307	LC3
Light Fastness	ISO 105 B02	5
Water fastness	ISO 105 B01	4
Rubbing fastness	ISO 105 X12	4
Salt water	ISO 105 E02	4
Shampoo	BS 1006	4
Organic solvents	ISO 105 X05	4
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals	
Surface flammability	ASTM D2859	Pass

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
60 cm x 90 cm		135 cm x linm
90 cm x 120 cm		150 cm x linm
90 cm x 150 cm		200 cm x linm
120 cm x 180 cm		
120 cm x 240 cm		