

PROBRASTE is a very elegant step nosing profile used to improve slip and slide resistance on the step. Made in natural and polished brass or natural and anodised silver aluminium, the upper part is knurled to increase adherence. Compulsory in public buildings to comply with accident-prevention regulations. Recommended for elegant, refined surroundings and for steps in wood, tiles, melamine-coated/laminated wood, marble or natural stones. Width: 8, 10, 12,5 mm.

PROBRASTE

KNURLED NATURAL AND POLISHED BRASS
NATURAL AND ANODISED SILVER ALUMINIUM



NATURAL BRASS thermo packed
bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PBPON 10	10		*
PBPON 125	12,5		*

POLISHED BRASS thermo packed
bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PBPOL 10	10		*
PBPOL 125	12,5		*




NATURAL ALUMINIUM thermo packed
bar length 2,7 lm - pack 20 Pcs - 54 lm


Article	H mm		
PBPAN 08	8		
PBPAN 10	10		
PBPAN 125	12,5		

ANODISED SILVER ALUMINIUM thermo packed
bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PBPAA 08	8		
PBPAA 10	10		
PBPAA 125	12,5		




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the PROBRASTE in the required width and colour according to the thickness of the tile (stairs).
 2. First fix the riser part, placing it at the correct and final height.
 3. Fill the empty spaces under the profile with the tile adhesive.
 4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile.
 5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive.
- Oxidation marks in the polished/natural brass range may be easily removed with specific chemical products (Sidel-Smac).

COLOURS



* = On demand, price and delivery time to be agreed.