
SKIRTING

NON-TOXIC FLEXIBLE VINYL RESIN in 6 COLOURS

PVC FLEXIBLE SKIRTING height 60 mm and 120 mm, is a very strong profile ideal for easily achieving special, attractive, superior finishes. Installation recommended with glue or silicone. Easy to install, the shaped edges ensure perfect adhesion to the surface. The projecting rounded flange covers the terminal expansion joint.

Colours: white - light grey - dark grey - dark brown - brown - black




ATTENTION: IN ORDER TO USE, LAY AND FIX PROPERLY THIS PRODUCT PLEASE LOOK AT **OUR WEBSITE OR APP LAYING / FIXING VIDEO** FOR CORRECT INSTALLATION



NON-TOXIC FLEXIBLE VINYL RESIN rolls length 50 LM

	Article	H mm			
€	BTPV 60 A Adehsive	60			
Э	BTPV 120 A Adehsive	120			
	BTPV 60	60			
	BTPV 120	120			
	Available in the colours: B - GC - GS - T - M - N. The code of the selected colour must be added to the article code. E.g.: BTPV 60 (chosen colour Light Grey) BTPVGC 60.				



1. Choose the skirting of the required height 60/120mm and choose the colour. 2. Lay the profile, taking care to calculate the width of the insideductade corners (for the H: 60 mm version only). 3. Lay the skirting using an adhesive suitable for gluing flexible PVC onto mortar, plaster, accessorised walls, etc. or fix with screwshalls.

As regards the items with adhesive, the adhesive roll is sold separately (50 lm for H:60), (100 lm for H:120)

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)

B - White	GC - Light Grey	GS - Dark Grey	T - Dark Brown	M - Brown	N - Black

SKIRTING 62F is a new 62 mm skirting board made of non-toxic, flexible vinyl resin. This profile is very resistant and particularly sulted for providing highly aesthetic perimeter skirting of excellent quality at reasonable prices. It differs from the BTPV. 60 skirting board in that it is provided with a bottom flange that allows it to be placed perpendicularly (90°) to the wallfilling and well-placed perpendicularly (90°) to the wallfilling and (90°) to the wallfill

addition, the horizontal flange covers the floor's perimeter expansion joint. We recommend applying the skirting using glue/adhesive/

Bostik/mastic. Alternatively, you can choose the self-adhesive version for quick, effortless installation.

INSIDE and OUTSIDE CORNERS

NON-TOXIC FLEXIBLE VINYL RESIN - 6 COLOURS

FLUSH CORNERS

IN/OUTSIDE CORNER for FLEXIBLE SKIRTIG - pack, 10 Pcs

Article	H x L mm			
RIBF 60 (inside)	60 X 60		,	
REBF 60 (outside)	60 X 43			
Available in the colours: B - GC - GS - T - M - N.				

The code of the selected colour must be added to the article code E.g.: RIBF... 60 (chosen colour Light Grey) RIBFGC 60.






The color of the corners may be slightly different from the skirting.

SKIRTING 62F

REBF... 60

FLEXIBLE VINYL RESIN in 6 COLOURS

RIBF... 60



LAYING INSTRUCTIONS

LAYING INS HIGH TIONS

1. Choose the colour of the skirting board, indicating whether you want it with
or without a self-adhesive backing, 2. Cut the skirting to length, taking into
account the width of the internal and external connections, 3. Self-adhesive
skirting is recommended only for surfaces that are perfectly smooth, nonoily and non-porous. On plaster and mortar surfaces, use a non-ad version and apply the skirting using quick-setting acrylic silicone suitable for gluing aluminium to mortar, plaster, etc.

ATTENTION: IN ORDER TO USE, LAY AND FIX PROPERLY THIS PRODUCT PLEASE LOOK AT OUR WEBSITE OR APP LAYING / FIXING VIDEO FOR CORRECT INSTALLATION

FI FXIBI F VINYI RESIN

rolls length 50 LM with or without adhesive

Article	H mm	
BTPF 62A (with adhesive)	62	
BTPF 62	62	

Available in the colours: B - GC - GS - T - M - N The code of the selected colour must be added to the article code. E.g.: BTPF...62 (chosen colour Light Grey) BTPFGC 62.

As regards the items with adhesive, the adhesive roll is sold separately (50 lm)

COLOURS

