SKIRTING 7016

FOAMED VINYL RESIN 32 WOOD FINISHES, AND 3 IN SOLID COLOUR

BTEPRS/385/100 BTEPR... 7016 11,27 mm 70 mm 16 mm

SKIRTING 7011

FOAMED VINYL RESIN 32 WOOD FINISHES, AND 3 IN SOLID COLOUR



FOAMED VINYL RESIN (wood finishes - black - white and silver) bar length 2.5 LM - pack, 20 Pcs - 50 LM

	Article	Hmm	
\bigcirc	BTEPR 7016	70	

Available in the finishes : 04W-05W-06W-07W-08W-09W-10W-11W-13W-18W-21W-25W-28W-29W-30W-31W-32W-33W-34W-35W-36W-37W-38W-39W-40W-41W-42W-43W-44W-45W-46W-47W

-B-N-AA. The code of the selected colour must be added to the article code. E.g.: BTEPR... 7016 (chosen finish Dark beech) BTEPR04W 7016.

INSTRUCTIONS FOR LAYING METHODS

1. Choose " SKIRTING" in the desired finish. 2. Fix the pre-punched support to the wall with screws every 50 cm. 3. Attach the profile to the support applying low pressure. 4. Alternatively fix the profile using a suitable fast adhesive, nails or screws

O = News 2016

Article BTEPR... 7011



SUPPORT / FIXING CLIP - PLASTIC support lenght 5 cm - pack. 100 Pcs

	Article	Hmm	
0	BTEPRS 385/100	37,5	


Order the SUPPORT and choose the SKIRTING in the desired finish



SKIRTING 7011 is a vinyl resin foam profile with a height of 70 mm x 10,5mm, available in 32 different wood effect finishes and 3 finishes standard colours that could be matched with the PROINSERT SYSTEM's profiles. Suitable as skirting/Basebord for floating and glued wood floor, laminate and LVT, could be laid with suitable adhesive, or else with nails

SKIRTING 7016 is a vinyl resin foam profile with a height of 70 mm, available in 32 different wood - effect finishes and 3 finishes in solid colour that could be matched with the PROINSERT SYSTEM's profiles. The profile, suitable like skirting for floating and glued wood floor, laminate and LVT, could

be laid with suitable adhesive, and so can be support fixed to the wall with screws every 50 cm. Its special section, that allows to cover a 16 mm perimetral joint, and wide rance of finishes make it a very requested, elegant and econimic skirting board profile.



INSTRUCTIONS FOR LAYING METHODS

 Choose the skirting in the required the colour. 2. Lay the skirting using quick-setting suitable adhesive for gluing flexible PVC onto mortar-plaster-accessorised walls, etc. or fix with nails.

> PROGRESS® OFILES



FOAMED VINYL RESIN (wood finishes - black - white and silver) bar length 2,5 LM - pack. 20 Pcs - 50 LM

70



Available in the finishes : 04W-05W-06W-07W-08W-09W-10W-11W-13W-18W-21W-25W-28W-29W-30W-31W-32W-33W-34W-35W-36W-37W-38W-39W-40W-41W-42W-43W-44W-45W-46W-47W-B-N-AA. The code of the selected colour must be added to the article code. E.g.: BTEPR ... 7011 (chosen finish Dark beech) BTEPR04W 7011.

