

# 4Earth Anti Slip Mineral Tile

## User Safe Wash On Wash Off Anti Slip Treatment

For use with - Ceramic Tiles, Terrazzo, Quarry Tile, Slate, Granite, Polished Stone, Travatine and most Marbles

### 4Earth Polish & Seal:

- Unsurpassed Slip Resistance
- Does not change aesthetics of the floor
- Easy Maintenance and Cleaning
- Proven Durability
- Easy and Fast Application
- No Curing Time
- Keeps Floors Safer For Longer

### Application

It is advised a test area is conducted before any large area is coated.

Ensure the floor is clean, completely dry and free from contaminants prior to application.

Apply 4Earth Mineral Tile to area ensuing it is soaked, using a sprayer or mop. We strongly recommend that only small areas are treated at a time, around 30m<sup>2</sup>, before moving onto the next area.

Leave to dwell for 15-60 mins, again making sure the product does not dry. When the appropriate dwell time has lapsed you can then begin to rinse the product using a separate sparyer with clean water. Spray the full area that has been anti slipped. This should then be quickly lifted from the floor using a scrubber dryer or a wet vac.

A mop with clean water can be used to collect any excess left behind by the wet vac / scrubber.

A detailed application guide is available from 4Earth Solutions Technical Team

### Maintenance

4Earth Anti Slip Mineral Tile should be maintained using 'The 4Earth Maintenance Pack'.

This will not impact your daily cleaning regime but simply replace cleaning products with ones that carry anti slip properties.

Available at [4earthcleaningsupplies.com](http://4earthcleaningsupplies.com).

### Technical Data

Description:	Liquid
Colour:	Clear
pH-value:	4.5 NOMINAL
Odour:	Mild
Recoat Time:	N/A
Drying time:	N/A
Light traffic:	Immediately
Coverage:	8m <sup>2</sup> per litre. (surface dependant)
Packed:	5 litres / 25 Litres
Pot Life:	5 Years
Shelf Life:	5 Years
Pack Make Up:	Single Pack
Storage:	Store in a dry place not not below 5°C

