



4Earth Super Seal

Super Strong Bonding Sealer & Anti Slip

For use on polished porcelain, granite & polished concrete

4Earth Super Seal provides:

- Excellent scratch resistance
- 36+ Wet PTV (Anti Slip Version)
- Easy to apply
- UV Stable
- Low VOCs
- 1st coat dry in as little as 30 - 40 minutes
- One Pack
- Extremely easy to clean and maintain

Application

It is advised a test area is conducted before any large area is coated.

Shake bottle well before use. Product should not be used in temperatures less than 10°C

Ensure the floor is clean, dry and free from contaminants prior to application.

Use a microfibre roller to apply in a uniform manner. Do not allow product to puddle.

Some surfaces may need to be keyed before application.

A detailed application guide is available from 4Earth Solutions on request.

Maintenance

Sweep regularly to remove abrasive dirt and grit from surface and clean using a neutral pH detergent (available from 4Earth Solutions).

For maximum floor safety, ensure all cleaning solution is thoroughly rinsed from the surface using a fresh mop or scrubber dryer.

In extreme cases, should signs of wear appear, a maintenance coat can be applied. 4Earth Solutions technical department are available to advise on all queries.

Technical Data

Available Finish:	Matt, Satin and Gloss
Solids content:	34 - 36%
pH-value:	7.5 - 8.5
System Thickness (dry)	25 Microns
Recoat Time:	1 - 2 hours
Drying time:	1 - 2 hours at 20°C
Light traffic:	Up to 12 Hours
Medium traffic:	12 - 24 hours
Full cure:	72 hours
Coverage:	8m ² per litre. (surface dependant)
Packed:	5 litres
Pot Life:	8 Weeks (minimum)
Shelf Life:	2 Years
UV Resistance:	Excellent
Scratch Resistance:	Excellent
Chemical Resistance:	Excellent
Pack Make Up:	Single Pack
Storage:	Store in a dry place not below 5°C