



PROLEVAL 25-35-38 are joint – covers in anodised aluminium with gold, silver and bronze finish in various widths with a more or less knurled flat surface, available with self-adhesive backing or punched in various lengths. They are used to join floors of the same or differing material e.g. ceramic tiles, wood, marble, parquet or laminated, mainly to cover flaws created during laying or expansion joints. The chamfered edges ensure perfect adhesion to the floor, while the flat top allows perfect door closure. Recommended for dwellings and public environments with intense pedestrian traffic. Easy to lay, the high-strength elastomer adhesive ensures an excellent grip.

PROLEVAL 25-35-38

ANODISED GOLD, SILVER AND BRONZE ALUMINIUM WITH SELF-ADHESIVE AND PUNCHED



ANODISED ALUMINIUM with adhesive thermo packed
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	Width mm
PLV... 25A	25
PLV... 35A	35
PLV... 38A	38

Available in the colours: AA - AO - AT - CH - SB.
The code of the selected colour must be added to the article code.
E.g.: PV... 25A (chosen finish anod. silver) PLVAA 25A.



ANODISED ALUMINIUM punched thermo packed
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	Width mm
PLV... 25F	25
PLV... 35F	35
PLV... 38F	40

OFF-CENTRE HOLES ON DEMAND
PLV... 25F, PLV... 35F available in the colours: AA - AO - AT - CH - SB.
The code of the selected colour must be added to the article code.
E.g.: PV... 25F (chosen finish anod. silver) PLVAA 25A.

ANODISED ALUMINIUM with adhesive thermo packed - bar length 0,93 lm - pack 20 Pcs 

Article	Width mm
PLVAA 259AS	25
PLV... 359AS	35
PLV... 389AS	38

ANODISED ALUM. punched with screws and screw anchors thermo packed - bar length 0,93 lm - pack 20 Pcs 

Article	Width mm
PLV... 259FS	25
PLV... 359FS	35
PLV... 389FS	38

PLV... 389FS available in the colours: AA - AO - AT - CH - SB.
The code of the selected colour must be added to the article code.
E.g.: PV... 389FS (chosen finish anod. silver) PLVAA 25A.

ANODISED ALUMINIUM with adhesive thermo packed - bar length 1,03 lm - pack 20 Pcs 

Article	Width mm
PLV... 3510AS	35

ANODISED ALUM. punched with screws and screw anchors thermo packed - bar length 1,03 lm - pack 20 Pcs 

Article	Width mm
PLV... 3510FS	35

ANODISED ALUMINIUM with adhesive thermo packed - bar length 1,66 lm - pack 20 Pcs 

Article	Width mm
PLV... 3516AS	35

ANODISED ALUM. punched with screws and screw anchors thermo packed - bar length 1,66 lm - pack 20 Pcs 

Article	Width mm
PLV... 3516FS	35

Available in the colours: AA - AO (AB, AT, CH and SB available on demand with a minimum quantity order of 270 lm).
The code of the selected colour must be added to the article code. E.g.: PLV... 25A (chosen colour anodised gold alum.) PLVAO 25A.

COLOURS




AA - Anodised silver alum. AO - Anodised gold alum.

ON DEMAND MINIMUM 270 LM by color and height




AB - Anodised bronze alum. AT - Anodised titanium alum. CH - Anod. champagne alum. SB - Anod. sand aluminium (price and delivery time to be agreed)



threshold - joint-cover profiles

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
 2. Degrease, wash and clean the solid surface thoroughly.
 3. Remove the protective paper from the adhesive.
 4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.
- Adhesive version**
1. Mark the position of the holes using the existing holes in the profile as reference.
 2. Mark the position of the holes using the existing holes in the profile as reference.
 3. Insert the screw anchors into the drilled holes.
 4. Fix the profile using flathead screws suitable for the relative slots in the profile.

* = On demand, price and delivery time to be agreed.