



PROLINOLEUM is a self-adhesive transition profile in anodised aluminium with gold/silver finish. It is used to give a clean-cut, elegant finish to hardwearing surfaces in PVC or linoleum and other thin materials between 2-3 mm thick. **PROLINOLEUM** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay, the high-strength elastomer adhesive ensures an excellent grip.

PROLINOLEUM

ANODISED GOLD AND SILVER ALUMINIUM
WITH AND WITHOUT SELF-ADHESIVE



ANODISED GOLD AND SILVER ALUMINIUM thermo packed

bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H x L mm
PLU ... 16 (without adhesive)	2,5 X 16
PLU ... 16A (with adhesive)	2,5 X 16

Available in the colours: AA (AO, AT, CH and SB available on demand with a minimum quantity order of 270 lm). The code of the selected colour must be added to the article code.
E.g.: PLU ... 16 (chosen finish anod. gold) PLUAO 16.

COLOURS



AA - Anodised silver alum.


AVAILABLE MINIMUM QUANTITY 270 LM by color and height




AO - Anodised gold alum.



AT - Anodised titanium alum.



CH - Anod. champagne alum.




SB - Anod. sand aluminium

(price and delivery time to be agreed)

PLU ... 16
PLU ... 16A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

profiles for low thicknesses

PROFLOOR 24 is a self-adhesive transition profile with chamfered edges in stainless steel 1.4016 and polished brass with protective film. It is used to give a clean-cut, elegant finish to hardwearing surfaces in PVC and linoleum - carpeting and other thin materials between 2. and 5mm thick. **PROFLOOR 24** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay, the high-strength elastomer adhesive ensures an excellent grip.

PROFLOOR 24

POLISHED STAINLESS STEEL AISI 304/1.4301
AND POLISHED BRASS WITH SELF-ADHESIVE



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H x L mm
PFRAC 24A	2/4,5 X 30

POLISHED BRASS self-adhesive thermo packed bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H x L mm
PFROL 24A	2/4,5 X 30

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs

Article	H x L mm
PFRAC 249AS	2/4,5 X 30

POLISHED BRASS self-adhesive thermo packed bar length 0,93 lm - pack. 20 Pcs

Article	H x L mm
PFROL 249AS	2/4,5 X 30

COLOURS



AC - Polished stainless steel AISI 304/1.4301-V2A




OL - Polished brass


On demand hand-brushed stainless steel
(prices and delivery time to be agreed)

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PFRAC 24A/249A
PFROL 24A/249A



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

profiles for low thicknesses