



TECHNICAL DATA SHEET

Modular Tile Mat 16 mm

TILE MATERIAL:	<ul style="list-style-type: none">- UV-resistant, hardwearing and elastic PVC- Hardness Shore A 75- Oil resistance Excellent- Electrical resistance Good insulator- UV- resistance Excellent
MODULAR TILES:	<ul style="list-style-type: none">- Tile size 400 x 140 mm- Hidden interlocking connectors, seamless look- Open grid, heel proof- Suitable for indoor and outdoor applications
WEIGHT:	- 9,8 kg / m ²
HEIGHT:	- 16 mm
TILE COLOUR:	- Dark grey
PACKAGING:	- 20 tiles / plastic foil (= ca. 1 m ²)
TEMPERATURE RESISTANCE:	- -20°C - +70°C
ROLLING LOAD:	- KfB dynamic test: 350 kg per wheel
SLIP RESISTANCE:	<ul style="list-style-type: none">- Conforms to DIN 51130 classification R 10- Average total acceptance angle 13,7°
FIRE CLASSIFICATION:	- Bfl-s1: EN ISO 11925-2, EN ISO 9239-1, EN 13501-1
EMISSIONS:	- ISO 16000-9: TVOC 330 µg/(m ² h). Class A+
MAINTENANCE:	- Easy to roll-up the mat for cleaning
GUARANTEE:	- 5 years / 5 million footsteps durability warranty

