

# 4Earth Polish & Seal

## Water Based 'Wet Look' Acrylic Floor Seal

For use on Terrazzo, Stone, PVC, Lino, Cork, Sealed Wood, Asphalt, Thermoplastic

### 4Earth Polish & Seal:

- Easy to apply
- 1st coat dry in as little as 30 minutes
- One Pack
- Extremely easy to clean and maintain
- Repels dirt and water
- Protects against colour fade
- Protect against corrosion

### Application

It is advised a test area is conducted before any large area is coated.

Ensure the floor is clean, completely dry and free from contaminants prior to application. Remove any existing polish with 4Earth Mop & Strip.

Apply a thin coat using a mop, cloth or sponge. This will seal the floor. A second coat will leave a gloss finish and a third coat will leave a high gloss finish. Leave 30 minutes between coats.

Once the final coat is applied leave 2 hours to allow the sealer to fully dry.

1 litre will cover 60m<sup>2</sup>.

### Maintenance

Sweep regularly to remove abrasive dirt and grit from surface and clean using a neutral pH detergent (available from 4Earth Solutions).

For maximum floor safety, ensure all cleaning solution is thoroughly rinsed from the surface using a fresh mop or scrubber dryer.

In extreme cases, should signs of wear appear, a maintenance coat can be applied. 4Earth Solutions technical department are available to advise on all queries.

### Technical Data

Available Finish:	Gloss / High Gloss
Specific Gravity:	1.03G/L
pH-value:	6 - 8
Colour:	Off White Liquid
Recoat Time:	30 minutes
Drying time:	1 - 2 hours at 20°C
Light traffic:	2 Hours
Coverage:	60m <sup>2</sup> per litre. (surface dependant)
Packed:	5 litres
Pot Life:	8 Weeks (minimum)
Shelf Life:	2 Years
Pack Make Up:	Single Pack
Storage:	Store in a dry place not below 5°C

