





Indoor Contract and Installation Matting Munster XT



Munster XT




Anthracite (CH)



Cobalt (BU)



Granite (GT)



Slate Grey (GY)



Mocha (BR)



Indoor Contract and Installation Matting

Munster XT

Premium quality barrier matting, designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas, including wall-to-wall applications.

Our new classic barrier mat, known for its softer yarns, has been enhanced with a mono-filament to offer additional scraping and provide excellent cleaning and absorbing. The new tri-colour grit pattern provides outstanding dirt-hiding characteristics.

Great ability to retain moisture (>5.8 litres per m²) and scrape debris from foot traffic while maintaining its great looking appearance for the longest time. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, public buildings, schools, universities, hospitals, department stores, banks, restaurants and on stairs.

Specifications:

- Densely tufted cut loop pile (81.000 tufts per m²) consisting of 100% polyamide 6 yarns.
- 850 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 9 mm.
- Weight: 3.6 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Full rolls:

- 135 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 135 cm per linear meter
- 200 cm per linear meter

Colours:

- Anthracite (CH)
- Cobalt (BU)
- Granite (GT)
- Slate Grey (GY)
- Mocha (BR)

Cleaning tip:

- Vacuum/shampooing or use injection/extraction method to clean.

Art. Nr.	Sizes	Weight kg
380R0051..	135 cm x 20 m	94,6
380C0051..	135 cm x 1m	4,7
380R0078..	200 cm x 20 m	145,6
380C0078..	200 cm x 1m	7,3

Anthracite (CH), Slate Grey (GY), Granite (GT), Cobalt (BU), Mocha (BR)

Product Testing

Water Retention

Crush Resistance

Dust Control

GOOD BETTER BEST SUPERIOR



Munster XT

GENERAL DESCRIPTION

Designation	Dust Control Matting		
Type	Contract carpet		
Description	Absorbent carpet mat		
Category	Indoor absorbent - Contract		
Recommended Use	Indoor - heavy traffic conditions		
Colours	Anthracite (CH), Slate Grey (GY), Cobalt (BU), Granite (GT), Mocha (BR)		
Dimensions	Standard Sizes	Full Rolls	Custom Lengths
	N/A	135 cm x 20 m 200 cm x 20 m	135 cm x linm 200 cm x linm
Special Remarks	Widths are including vinyl borders of 2,5 cm on each side		
Accessories	Bevelled Nosing 2 mm		

TECHNICAL SPECIFICATIONS

Pile Material	100% Polyamide
Backing	Black vinyl (DOP free)
Primary Backing	Nonwoven PET/PA
Process	Tufting
Yarn Construction	Velours cut loop pile
Pile weight	850 g/m ²
Total weight	3.5 kg/m ²
Pile height	7 mm
Total height	9 mm
Pile density	Awaiting results
Number of tufts	81,000

TESTS

Absorption Capacity	TNO W6034	5.8 l/m ²
Fire Rating	EN 13501	Cfl-S1
Slip Resistance	EN 13893	DS
Static charge	ISO 6356	< 0.1
Comfort	EN 1307	LC2
Suitability for stairs	EN 1963	Intensive use
Suitability for castor chairs	EN 985	Intensive use
Dimensional stability	ISO 2551	<0.4
Light fastness	ISO 105 B02	>6
Water fastness	ISO 105 B01	4
Rubbing fastness	ISO 105 X12	4
Salt water	ISO 105 E02	4
Shampoo	BS 1006	4
Organic solvents	ISO 105 X05	4
Sustainability	<ul style="list-style-type: none"> • Recyclable material • REACH compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) • Contributes to cleaner environment by reducing need of cleaning chemicals 	